

## Vertical Contact Toaster | VCT



**VCT-2000**



with wide mouth  
bun feeder



with motorized  
butter wheel and  
bun feeder



with heated base

For more than 25 years, the Vertical Contact Toaster has been a staple in foodservice operations, building a reputation for quality, performance, and reliability throughout the world.

The Vertical Contact Toaster gives buns a consistent, golden brown finish so they don't soak up the juices of the ingredients, helping the sandwich stay firm and delicious. With a dual-sided platen, the Vertical Contact Toaster has more capacity than conventional single-sided toasters, allowing operations to quickly serve fresh products to customers without making them wait.

The VCT-2000 features a digital controller for making precise adjustments to the quality of the toast for different bread products. A built-in auxiliary heater warms the top sides of the buns to help keep the assembled sandwich warmer for longer.

The VCT-2000 also includes belt wraps to minimize bun marking. Available features for the unit include a wide mouth bun feeder, motorized butter wheel, heated base, and back plate.

### FEATURES

- Dual-sided platen for additional toasting capacity compared to conventional single-sided toasters.
- Auxiliary heater warms top side of buns.
- Digital controller to adjust temperature of the platen.
- Space-saving vertical design.
- Continuously moving conveyor for immediate toasting.
- Separate compression adjustments for the heel and the crown.
- Release sheets allow buns to move easily down the heated platen without sticking or slipping.
- Easy to operate and clean.
- Stainless steel construction.
- Available toasting times range from 10 to 28 seconds.
- Additional features available, including wide mouth bun feeder, butter wheel, and heated base.

# Vertical Contact Toaster | VCT

## Dimensions

Model & Mfg. No.	Width (A)	Depth (B)	Height (C)
VCT-2000			
9210100			
9210114	21 1/4"	15 1/4"	23 1/4"
9210118	(540 mm)	(387 mm)	(591 mm)
9210200			
9210224			
VCT-2000			
9210116			
9210121	21 1/4"	15 1/4"	24 1/4"
9210123	(540 mm)	(387 mm)	(616 mm)
9210203			
9210212			
VCT-2000			
9210300			
9210304	21 1/4"	10 3/4"	23 1/4"
9210400	(540 mm)	(273 mm)	(591 mm)
9210402			

## Shipping Dimensions

Model & Mfg. No.	Height	Width	Depth	Weight
VCT-2000				
9210116				
9210121	33"	26"	16"	88 lbs.
9210123	(838 mm)	(660 mm)	(406 mm)	(40 kg)
9210203				
9210212				
VCT-2000				
9210100				
9210114				
9210118				
9210200	24"	22"	15"	75 lbs.
9210224	(610 mm)	(559 mm)	(381 mm)	(34 kg)
9210300				
9210304				
9210400				
9210402				

## Bun Specifications

Model & Mfg. No.	Feeder Opening	Crowns		Heels	
		Min.	Max.	Min.	Max.
VCT-2000					
9210100					
9210114					
9210118					
9210200	1 3/4"	1/2"	7/8"	1/2"	7/8"
9210300	(44 mm)	(13 mm)	(22 mm)	(13 mm)	(22 mm)
9210304					
9210400					
9210402					
VCT-2000					
9210116					
9210121					
9210123	1 3/4"	3/4"	1 1/8"	5/8"	1"
9210203	(44 mm)	(19 mm)	(29 mm)	(16 mm)	(25 mm)
9210212					
9210224					

## Specifications

Model & Mfg. No.	Pass Through Time	Volts	Watts	Amps	Hertz	Plug Description
<b>VCT-2000</b>						
VCT-2000						
9210100	10 sec.	208	3201	15.8	50/60	NEMA 6-20P 20 Amp, 250 Volt
VCT-2000						
9210200	10 sec.	220-240	3019-3593	13.7-15	50	CEE 7/7 16 Amp., 250 Volt
<b>VCT-2000 with Wide Mouth</b>						
VCT-2000						
9210116	10 sec.	208	3291	15.8	60	NEMA 6-20P 20 Amp, 250 Volt
VCT-2000						
9210121	17 sec.	208	3291	15.8	60	NEMA 6-20P 20 Amp, 250 Volt
VCT-2000						
9210123	28 sec.	208	3291	15.8	60	NEMA 6-20P 20 Amp, 250 Volt
VCT-2000						
9210203	17 sec.	220-240	3019-3593	13.7-15	50	CEE 7/7 16 Amp., 250 Volt
VCT-2000						
9210212	10 sec.	220-240	3019-3593	13.7-15	50	CEE 7/7 16 Amp., 250 Volt
<b>VCT-2000 with Motorized Butter Wheel</b>						
VCT-2000						
9210114	10 sec.	208	3291	15.8	50/60	NEMA 6-20P 20 Amp, 250 Volt
VCT-2000						
9210118	17 sec.	208	3291	15.8	50/60	NEMA 6-20P 20 Amp, 250 Volt
<b>VCT-2000 with Wide Mouth and Motorized Butter Wheel</b>						
VCT-2000						
9210224	10 sec.	220-240	3019-3593	13.7-15	50	IEC-309 16 Amp., 230 Volt Pin & Sleeve
<b>VCT-2000 with Heated Base</b>						
VCT-2000						
9210300	10 sec.	208	3326	16	50/60	NEMA 6-20P 20 Amp, 250 Volt
VCT-2000						
9210400	10 sec.	220-240	3058-3640	13.9-15.2	50/60	CEE 7/7 16 Amp., 250 Volt IEC-309
VCT-2000						
9210402	10 sec.	220-240	3058-3640	13.9-15.2	50/60	16 Amp., 230 Volt Pin & Sleeve
<b>VCT-2000 with Heated Base and Back Plate</b>						
VCT-2000						
9210304	10 sec.	208	3326	16	50/60	NEMA 6-20P 20 Amp, 250 Volt

## Accessories

Bun Feeder (P/N 7000236): An automatic gravity-fed bun feeder.

Bun Feeder (P/N 7000787): An automatic gravity-fed bun feeder for use in wide-mouth toasters.

Butter Wheel (P/N 7000238): Stainless steel butter wheel and pan.

Butter Wheel (P/N 7000703): Stainless steel butter wheel and pan for use in wide-mouth toasters.

Low-Profile Bun Feeder (P/N 7000292): Low profile bun feeder allows for quick and easy loading of buns into the toaster.

P/N 1020231 05/17